

PRODUCT DATA SHEET

Sikalastic®-500 Acrylic Primer HK

WATER BASED ACRYLIC PRIMER

DESCRIPTION

Sikalastic®-500 Acrylic Primer HK is used as a primer, sealer and bonding agent to prepare floor surfaces prior to the application of waterproofing membrane and wall coating system.

USES

- Act as a bonding agent to old floors
- Prime and use as a bonding agent on smooth concrete finishes
- Seal pores on rough porous concrete to eliminate air bubble
- Reduce dust and increase abrasion resistance of the substrate

CHARACTERISTICS / ADVANTAGES

- Water base
- Easy to apply

PRODUCT INFORMATION

Packaging	4 kg/pail, 20 kg/pail
Shelf Life	12 months from the date of production
Storage Conditions	Stored properly in undamaged and unopened original sealed packaging in cool and dry conditions. Protect from direct sunlight and frost.

TECHNICAL INFORMATION

Reaction to Fire	Non Flammable
------------------	---------------

APPLICATION INFORMATION

Yield	5–10 m ² per litre depending on the substrate condition
Drying Time	30 min

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Ensure that surface are dry and clean and free from curing compound or release agents. No chipping or roughening of surface is required if the condition is stable. Old paint work which are stable can remain. Any contamination including commercial detergents used for cleaning must be thoroughly rinsed off with plenty of water.

APPLICATION

Apply Sikalastic®-500 Acrylic Primer HK to clean floor with roller, brush and squeegee. Allow to dry till clear film appears. Primer is dry when all milkiness disappears.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

SIKA HONGKONG LTD.

Rm.1507-12, Blk A, New Trade Plaza,
6 On Ping Street, Shatin, N.T., H.K.
Phone: +852 26868108
Fax: +852 26453671
Mail: marketing@hk.sika.com
Website: www.sika.com.hk



Product Data Sheet
Sikalastic®-500 Acrylic Primer HK
December 2020, Version 02.01
020915108010000013

Sikalastic-500AcrylicPrimerHK-en-HK-(12-2020)-2-1.pdf