

## PRODUCT DATA SHEET

# SikaProof® Sandwich Tape-80 AP

DOUBLE-SIDED ADHESIVE OVERLAP TAPE FOR THE SIKAPROOF 612 / 615 / 808 / 810 WATER-PROOFING SYSTEM

### DESCRIPTION

SikaProof® Sandwich Tape-80 AP is a double-sided adhesive tape based on a hot melt sandwiched between release liners.

### USES

SikaProof® Sandwich Tape-80 AP may only be used by experienced professionals.

- Sealing and bonding of overlap joints and details within the SikaProof® membrane system

### CHARACTERISTICS / ADVANTAGES

- High adhesion and sealing capability
- High durability
- Simple and fast to install

### PRODUCT INFORMATION

<b>Packaging</b>	5 rolls packed in one cardboard box
<b>Shelf Life</b>	12 months from date of production
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +40 °C. Always refer to packaging.
<b>Appearance / Colour</b>	Transparent hot melt and white release liners
<b>Length</b>	30 m
<b>Width</b>	80 mm
<b>Thickness</b>	0.8mm (±5 %)

### SYSTEM INFORMATION

<b>System Structure</b>	SikaProof® Sandwich Tape-80 AP is a system component for sealing overlap joints of the SikaProof® membrane system. For more detailed information, refer to Sika® Method Statement: SikaProof® System
<b>Compatibility</b>	For materials in direct contact (such as any synthetics etc.) the compatibility must be evaluated before full project application. Contact Sika® Technical Services for more information.

## APPLICATION INFORMATION

Ambient Air Temperature +5 °C min. / +45 °C max.

Substrate Temperature +5 °C min. / +60 °C max.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Do not install SikaProof® Sandwich Tape-80 AP during continuous or prolonged rain or snowfall.
- The substrate quality and conditions must be fulfilled, or appropriate measures must be taken.
- SikaProof® Sandwich Tape-80 AP is not permanently UV resistant.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

### SIKA HONGKONG LTD.

Rm.1507-12, Blk A, New Trade Plaza,  
6 On Ping Street, Shatin, N.T., H.K.  
Phone: +852 26868108  
Fax: +852 26453671  
Mail: marketing@hk.sika.com  
Website: www.sika.com.hk



Product Data Sheet  
SikaProof® Sandwich Tape-80 AP  
December 2022, Version 01.01  
020720308000000020

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The contact surfaces must be dry, clean and free of materials that could impair the adhesion. Contaminants, such as dirt, dust, oil, bitumen and debonding agents, such as surfactants and silicones must be removed.

### APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

SikaProofSandwichTape-80AP-en-HK-(12-2022)-1-1.pdf