

## PRODUCT DATA SHEET

# Sika® Reemat Premium

### Glass fibre reinforcement mat

#### DESCRIPTION

Sika® Reemat Premium is a glass fibre reinforcement mat for use with Sikalastic® Liquid Applied Membrane systems

#### USES

- Reinforcement for Sikalastic® and SikaRoof® MTC Systems
- Reinforcement for SikaRoof® MTC Detailing
- For roofs with complex geometry and detailing

#### CHARACTERISTICS / ADVANTAGES

- Easy and quick application
- Easy to adjust to complicated details
- Ensures the correct thickness of the base coat
- Improves crack-bridging properties of the system
- Improves mechanical properties of the system

#### APPROVALS / STANDARDS

- European Technical Assessment ETA 13/0456 based on ETAG 005 parts 1 and 6 - Liquid-applied roof waterproofing using kits based on polyurethane - Sikalastic®-614
- European Technical Assessment ETA 12/0316 based on - Membranes, including liquid applied and kits for water and/or water vapour control - Sikalastic®-618
- European Technical Assessment ETA 14/0177 based on - ETAG 005 parts 1 and 6 - Liquid-applied roof waterproofing using kits based on polyurethane - Sikalastic®-641
- European Technical Assessment ETA 09/0139 based on - ETAG 005 parts 1 and 6 - Liquid-applied roof waterproofing using kits based on polyurethane - SikaRoof®- MTC

#### PRODUCT INFORMATION

<b>Chemical Base</b>	Random glass fibre strand matting				
<b>Packaging</b>	Roll sizes: <table border="1"> <tr> <td>Length</td> <td>90 m</td> </tr> <tr> <td>Width</td> <td>0.3 and 1.25 m</td> </tr> </table> <p>Refer to current price list for packaging variations.</p>	Length	90 m	Width	0.3 and 1.25 m
Length	90 m				
Width	0.3 and 1.25 m				
<b>Shelf Life</b>	5 years from date of production				
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged packaging in dry conditions and temperatures between +5 °C and +35 °C. Always refer to packaging.				
<b>Appearance / Colour</b>	White				
<b>Mass per Unit Area</b>	225 g/m <sup>2</sup>				

# SYSTEM INFORMATION

## System Structure

For detailed information regarding system build-ups, refer to the System or Product Data Sheet of the relevant Liquid Applied Membrane

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LIMITATIONS

Refer to the Sika Method Statement of the relevant Liquid Applied Membrane system

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

Refer to the Sika Method Statement of the relevant Liquid Applied Membrane system

### APPLICATION

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Refer to the Sika Method Statement of the relevant Liquid Applied Membrane system

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

### SIKA HONGKONG LTD.

Rm.1507-12, Blk A, New Trade Plaza,  
6 On Ping Street, Shatin, N.T., H.K.  
Phone: +852 26868108  
Fax: +852 26453671  
Mail: marketing@hk.sika.com  
Website: www.sika.com.hk



### Product Data Sheet

Sika® Reemat Premium  
September 2024, Version 04.01  
020915952000000004

SikaReematPremium-en-HK-(09-2024)-4-1.pdf