

PRODUCT DATA SHEET

SikaProof® Tape-160 AP

Sealing and bonding cover strip

DESCRIPTION

SikaProof® Tape-160 AP is a sand cover strip, which is mainly made of polyolefin, resin and other polymer materials and has permanent non curing characteristics; It is a neutral sealing tape composed of sand, hot melt adhesive, PET film and PE release film.

USES

Sealing and bonding cover strip, connections and details within the SikaProof®-612 or SikaProof®-615.

CHARACTERISTICS / ADVANTAGES

- Excellent chemical resistance
- No flowing at high temperature
- No cracking at low temperature

PRODUCT INFORMATION

Packaging	160mm x 25 m/roll
Shelf Life	Under normal transportation and storage conditions, the shelf life is 12 months from the production date.
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures below 30°C. Store in a horizontal position. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage. Prevent tilting or side pressure during transportation, and cover the tablecloth if necessary. Always refer to packaging.
Appearance / Colour	white/transparent
Top Surface	white sand
Bottom Surface	PE release liner with Sika logo
Length	25m/Roll
Width	160mm
Thickness	1.2mm
System Structure	SikaProof® Tape-160 AP is a system component for sand cover strip of the SikaProof® membrane system. For more detailed information, refer to Sika® Method Statement: SikaProof® System

Compatibility

For materials in direct contact (such as any synthetics etc.) the compatibility must be evaluated before full project application. Contact Sika® Technical Services for more information.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

APPLICATION

- Clean the substrate to prevent the surface from being dirty and affecting the bonding effect.
- Tear off the release film of the required size and thickness, adhere it to the application part and compact it.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

SIKA HONGKONG LTD.

Rm.1507-12, Blk A, New Trade Plaza,
6 On Ping Street, Shatin, N.T., H.K.
Phone: +852 26868108
Fax: +852 26453671
Mail: marketing@hk.sika.com
Website: www.sika.com.hk



Product Data Sheet
SikaProof® Tape-160 AP
November 2023, Version 01.01
020720308000000015

SikaProofTape-160AP-en-HK-(11-2023)-1-1.pdf