

PRODUCT DATA SHEET

Ronafix® TS

ADMIXTURE FOR RONAFIX® COLOUR GROUT POWDER

DESCRIPTION

Ronafix® TS is a high performance water based SBR polymer for enhancing the waterproofing and bonding performance of Ronafix® Colour Grout Powder. It is suitable for all internal and external application where improved waterproofing, flexural and adhesive strength is required.

USES

- Internal and external application
- Swimming pools and water tanks

CHARACTERISTICS / ADVANTAGES

- Improved bond strength
- Improved waterproofing properties
- Water based

PRODUCT INFORMATION

Packaging	5 litres drum 30 litres drum
Shelf life	9 months from the date of production
Storage conditions	Stored properly in undamaged and unopened original sealed packaging in the temperature range +5 °C to +35 °C. Protect from direct sunlight and frost.

APPLICATION INFORMATION

Ambient Air Temperature	+5 °C to +35 °C
--------------------------------	-----------------

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Remove all adhesive, oil, dust and other loose material from within the tile joints. Ensure that joints are clean and dry. Check colour code on packaging and colour of contents to ensure correct colour grout powder is used.

MIXING

Place approximately 5 litres of Ronafix® TS into the mixing vessel. Slowly add the total contents of Ronafix® Colour Grout powder into the mixing vessel. Initially, mix continuously for at least 3 minutes using an electric drill with paddle, until all powder has been wetted out and a uniform homogeneous paste is achieved. Allow the mixture to rest for at least 5 minutes and re-mix the material for another 1 minute before applying the colour grout mixture to the tile joints. The mixed colour grout should be kept in the mixing vessel and protected from direct sunlight. The mixed colour grout should be used within 2 hours of initial mixing.

APPLICATION METHOD / TOOLS

Apply the colour grout with a rubber squeegee or rubber trowel. Work it into the tile joints with a diagonal or circular motion to ensure that the joints are completely filled with colour grout. Remove excess grout from the surface of the tile as the work proceeds. When the film of grout on the tile face is drying, use a damp but not wet rubber sponge to wipe off the film.

CLEANING OF EQUIPMENT

Clean all tools and application equipment with clean water immediately after use.

FURTHER INFORMATION

1. Staining of tiles, pavers, marble and stone may occur due to their nature. Confirm compatibility with a test area before grouting primary installation.
2. Standard Grade "Ronafix® Colour Grout" is not recommended for joint width below 3 mm.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

SIKA HONGKONG LTD.

Rm.1507-12, Blk A, New Trade Plaza,
6 On Ping Street, Shatin, N.T., H.K.
Phone: +852 26868108
Fax: +852 26453671
Mail: marketing@hk.sika.com
Website: www.sika.com.hk



Product Data Sheet

Ronafix® TS

February 2020, Version 01.02
021790501000000015

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet (MSDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

RonafixTS-en-HKRON-(02-2020)-1-2.pdf